

**Arrow 43 #**

Uses & Description

Arrow 43 is an asphalt saturated organic felt that is coated with a high quality asphalt coating. Arrow 43 is used as a base ply in a number of BUR applications and is non-perforated which makes it an ideal vapor retardant

Meets Florida Approval BFL # 2074



Specifications

<b>ASTM</b>	D 2626 -04
<b>UL</b>	TYPE 15
<b>BREAKING STRENGTH, min lbf/in (kN/m)</b>	
with fiber grain	35 (6.1)
across fiber grain	20 (3.5)
<b>PLIABILITY, tested with 1/2" (13mm) radius</b>	2 failures
<b>MOISTURE, at time of manufacturing</b>	2.0% max
<b>MASS OF COATING AND SURFACING, lbs/100 ft2 (g/m2)</b>	18 (878), min
<b>MASS OF DESATURATED FELT, lbs/100 ft2 (g/m2)</b>	5.2 (253)
<b>THICKNESS OF DESATURATED FELT, in. (mm)</b>	.025 (0.64) min
<b>MASS OF SATURANT SOLUBLE IN TRIOCHLOROETHYLENE, lbs/100 ft2 (g/m2)</b>	7.2 (350)
<b>MASS PERCENT OF MINERAL MATTER PASSING A 212-µm (no.70) SIEVE, based on the total mass of mineral-filled coating and mineral surfacing</b>	60 %, max